

# ***Bike-Lift***<sup>®</sup>



DARE TO DREAM

## LIFTS



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)





# ***Bike-Lift***<sup>®</sup>



DARE TO DREAM

## **CRUISER 750 GATE**

MADE IN ITALY



LIFTS



Gate

750/R



Long Ramp 84 cm



Designed to work on any cruiser bike, this lift grants maximum stability, safety and reliability.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	220x12 cm
Maximum load capacity	750 kg	Tabletop overall dimensions	220x99 cm
Maximum height	120 cm	Gate size	60x36 cm
Minimum height	19 cm	Run-up ramp size	84x44,5 cm
Safety locking choices	10	Overall dimensions	230x100 cm
Tabletop size	220x75 cm	Weight	260 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

CG-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
CG-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 232x102x30 cm Gross weight 270 kg



# ***Bike-Lift***<sup>®</sup>



DARE TO DREAM

## **CRUISER 750 SPLIT**

MADE IN ITALY



LIFTS



Gate



Split



Shown in Harley-Davidson official equipment catalogue. Approved for service use by Harley-Davidson. Here shown in the special HD version.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	170x12 cm
Maximum load capacity	750 kg	Tabletop overall dimensions	220x99 cm
Maximum height	120 cm	Gate size	60x36 cm
Minimum height	19 cm	Split size	39x75 cm
Safety locking choices	10	Run-up ramp size	84x44,5 cm
Tabletop size	220x75 cm	Overall dimensions	230x100 cm
		Weight	260 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

CS-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
CS-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 232x102x30 cm Gross weight 270 kg




# Bike-Lift®



DARE TO DREAM

## MAX 500

MADE IN ITALY



### LIFTS



Built-in electro-hydraulic pump



Hand control



Designed to work on any cruiser bike up to 500 kg.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting

Maximum load capacity	500 kg	Side tool gutters size	210x12 cm
Maximum height	100 cm	Tabletop overall dimensions	210x99 cm
Minimum height	19 cm	Run-up ramp size	62x44,5 cm
Safety locking choices	6	Overall dimensions	220x100 cm
Tabletop size	210x75 cm	Weight	220 kg

### AVAILABLE IN THE FOLLOWING VERSIONS


M-001	EXTERNAL HYDRAULIC FOOT PUMP
M-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
M-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 232x102x30 cm Gross weight 250 kg




# Bike-Lift®



DARE TO DREAM

## MAX 500 GATE

MADE IN ITALY



LIFTS



Gate



Approved for service use by Suzuki France and Spain and by Yamaha Motor Italy. Ideal to work on any Suzuki and Yamaha bike.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	210x12 cm
Maximum load capacity	500 kg	Tabletop overall dimensions	210x99 cm
Maximum height	100 cm	Gate size	60x36 cm
Minimum height	19 cm	Run-up ramp size	62x44,5 cm
Safety locking choices	6	Overall dimensions	220x100 cm
Tabletop size	210x75 cm	Weight	220 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

MG-001	EXTERNAL HYDRAULIC FOOT PUMP
MG-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
MG-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 232x102x30 cm Gross weight 250 kg



# Bike-Lift®



DARE TO DREAM

## SUPER MAX 500 GATE

MADE IN ITALY



LIFTS



Gate



11 safety locking choices.



Chosen by KTM for its own repair shop in Mattighofen. This lift reaches the outstanding height of 130 cm.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	210x12 cm
Maximum load capacity	500 kg	Tabletop overall dimensions	210x99 cm
Maximum height	130 cm	Gate size	60x36 cm
Minimum height	19 cm	Run-up ramp size	62x44,5 cm
Safety locking choices	11	Overall dimensions	220x100 cm
Tabletop size	210x75 cm	Weight	240 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

SMG-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
SMG-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 232x102x30 cm Gross weight 250 kg



# ***Bike-Lift***<sup>®</sup>



DARE TO DREAM

## **MAX 500 TWIN ARMS**

MADE IN ITALY



LIFTS



Footpeg bracket



Switching device



This unique and innovative lift allows to work on any sport bike easily and securely. Amazing time saving can be achieved with tire changing, suspension work and crash repairs. Wheel clamp W-36 S included

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Minimum height – Twin Arms	35	cm
Maximum load capacity – Lift	500 kg	Safety locking choices	6	
Maximum load capacity – Twin Arms	350 kg	Tabletop size	210x75	cm
Maximum height – Lift	100 cm	Tabletop overall dimensions	210x94	cm
Minimum height – Lift	19 cm	Run-up ramp size	62x44,5	cm
Maximum height – Twin Arms	70 cm	Overall dimensions	210x95	cm
		Weight	260	kg

### AVAILABLE IN THE FOLLOWING VERSIONS


MTA-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
MTA-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp, W-36 S, CB/L

### ACCESSORIES

Tie downs	Item no.: TD-1 B, STD B, R-1 B
Antiskid plate	Item no.: ASM-580

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 220x102x60 cm Gross weight 280 kg



# ***Bike-Lift***<sup>®</sup>




DARE TO DREAM

## **UNDER FRAME TWIN ARMS**

MADE IN ITALY



LIFTS



Lifting Platform



Platform with CB/L



Its wide lifting surface allows to easily raise all Harley-Davidson bikes maintaining them in a safe and secure horizontal position.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Tabletop size	220x75 cm
Maximum load capacity – Lift	750 kg	Tabletop overall dimensions	220x99 cm
Maximum load capacity – Twin Arms	500 kg	Run-up ramp size	85x44,5 cm
Maximum height – Lift	120 cm	Lifting platform size	77x38 cm
Minimum height – Lift	19 cm	Dimensioni Split	39x75 cm
Maximum height – Lifting platform	45 cm	Overall dimensions	230x100 cm
Safety locking choices	10	Weight	320 kg

### AVAILABLE IN THE FOLLOWING VERSIONS


UF/500	BUILT-IN ELECTRO-HYDRAULIC PUMP TABLETOP MAX 500
UF/750	BUILT-IN ELECTRO-HYDRAULIC PUMP TABLETOP CRUISER 750

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp, W-40, RM, CB/L

### ACCESSORIES

Tie downs	Item no.: TD-1 B, STD B, R-1 B
Antiskid plate	Item no.: ASM-580

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 235x105x40 cm Gross weight 340 kg



# Bike-Lift®



DARE TO DREAM

## SPORT 500 GATE

MADE IN ITALY



LIFTS



Gate



Approved for service use by Suzuki France and Spain and by Yamaha Motor Italy. Ideal to work on all sport bikes and maxi-scooters.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	210x12 cm
Maximum load capacity	500 kg	Tabletop overall dimensions	210x84 cm
Maximum height	100 cm	Gate size	60x36 cm
Minimum height	19 cm	Run-up ramp size	62x44,5 cm
Safety locking choices	6	Overall dimensions	220x85 cm
Tabletop size	210x60 cm	Weight	190 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

SG-001	EXTERNAL HYDRAULIC FOOT PUMP
SG-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
SG-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 225x90x30 cm Gross weight 210 kg



# Bike-Lift®



DARE TO DREAM

## SPORT 500 SPLIT

MADE IN ITALY



LIFTS



Gate



Split



Thanks to its swing down front portion, it allows easy removal of the forks in any sport bike.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	168x12 cm
Maximum load capacity	500 kg	Tabletop overall dimensions	210x84 cm
Maximum height	100 cm	Gate size	60x36 cm
Minimum height	19 cm	Split size	39x60 cm
Safety locking choices	6	Run-up ramp size	62x44,5 cm
Tabletop size	210x60 cm	Overall dimensions	220x85 cm
		Weight	190 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

SS-001	EXTERNAL HYDRAULIC FOOT PUMP
SS-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
SS-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 225x90x30 cm Gross weight 210 kg



# Bike-Lift®



DARE TO DREAM

## RACING 500

MADE IN ITALY



LIFTS



Run-up ramp



Air pump



Approved for service use by KTM.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	210x12 cm
Maximum load capacity	500 kg	Tabletop overall dimensions	210x84 cm
Maximum height	100 cm	Run-up ramp size	62x44,5 cm
Minimum height	19 cm	Overall dimensions	220x85 cm
Safety locking choices	6	Weight	140 kg
Tabletop size	210x60 cm		

### AVAILABLE IN THE FOLLOWING VERSIONS

RN-001	EXTERNAL HYDRAULIC FOOT PUMP
RN-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
RN-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 225x90x30 cm Gross weight 150 kg




# Bike-Lift®




DARE TO DREAM

## RACING 350

MADE IN ITALY



LIFTS



Electro-hydraulic pump



Foot pump



Specially designed for scooters and light sport bikes.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting		Side tool gutters size	200x12 cm
Maximum load capacity	350 kg	Tabletop overall dimensions	200x84 cm
Maximum height	100 cm	Run-up ramp size	62x44,5 cm
Minimum height	19 cm	Overall dimensions	200x85 cm
Safety locking choices	6	Weight	140 kg
Tabletop size	200x60 cm		

### AVAILABLE IN THE FOLLOWING VERSIONS

R-001	EXTERNAL HYDRAULIC FOOT PUMP
R-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
R-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Run-up ramp – Set of side tool gutters – Front safety bar

### ACCESSORIES

Wheel clamps	Item no.: W-32, W-34, W-36 S, W-38 S, W-40
Antiskid plate	Item no.: RM, PZA-60/75, ASM-580
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 225x90x30 cm Gross weight 150 kg




# Bike-Lift®




DARE TO DREAM

## FROG 500

MADE IN ITALY



LIFTS



Lift provided with adjustable rails to maintain four wheelers up to 500 kg.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting			Maximum internal distance between rails	74	cm
Maximum load capacity	500	kg	Minimum internal distance between rails	49	cm
Maximum height in Flat position	80	cm	Maximum external distance between rails	126	cm
Maximum height – Front section	100	cm	Minimum external distance between rails	102	cm
Maximum height – Rear section	155	cm	Safety locking choices	3	
Minimum height – Lift	19	cm	Run-up ramp size (two pieces)	82x24	cm
Rail size	200x26	cm	Overall dimensions	200x127	cm
			Weight	285	kg

### AVAILABLE IN THE FOLLOWING VERSIONS


F-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
F-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Two run-up ramps – Four wheel stops (two are fixed and two are sliding)

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 205x130x40 cm Gross weight 310 kg



# Bike-Lift®



DARE TO DREAM

## KODIAK 500

MADE IN ITALY



LIFTS



Rolling Platform



Conceived to service off-road vehicles up to 500 kg.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Maximum load capacity	500 kg	Safety locking choices	6
Maximum height	130 cm	Tabletop overall dimensions	45x33 cm
Minimum height	19 cm	Overall dimensions	190x78 cm
		Weight	110 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

KD-001	EXTERNAL HYDRAULIC FOOT PUMP
KD-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
KD-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110 Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

Tie downs TD-1 B

0

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 225x90x30 cm Gross weight 130 kg



# Bike-Lift®



DARE TO DREAM

## DUO 1000

MADE IN ITALY



LIFTS



External Electro-Hydraulic pump

DL-A01



Centre plate for three-wheel-vehicles with ramp

DL-A02



Special lifting device

New outstanding lift conceived for three/four-wheel-vehicles up to 1.000 kg.  
Ideal to work on Quads, ATV's, Ape Piaggio, microcar, golf cars and garden tractors when complete with all its accessories.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting

Maximum load capacity	1000 kg
Maximum height	130 cm
Minimum height	19 cm
Safety locking choices	12

Safety bar pneumatic release

Rail size (two pieces)	210x40 cm
Run-up ramp size (two pieces)	62x44,5 cm
Spacer bar	55x10 cm
Overall dimensions	220x135 cm
Weight (per lift)	120 kg

### CENTRE PLATE FOR THREE-WHEEL-VEHICLES (Item no. DL-A01)

Rail size	50x55 cm
Run-up ramp size	82x23 cm
Weight	15 kg

### AVAILABLE IN THE FOLLOWING VERSIONS

DL-003	BUILT-IN ELECTRO-HYDRAULIC PUMP
--------	---------------------------------

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard



### STANDARD EQUIPMENT

2 Run-up ramp – 1 Spacer bar (length 55 cm)

### ACCESSORIES

Centre plate for three-wheel-vehicles. Delivered complete with a run-up ramp.

Special lifting device

Tie downs

Antiskid Plate

### STANDARD PACKING

nr. 2 Thick carton box equipped with wood pieces at the bottom

Item no.: DL-A01

Item no.: DL-A02

Item no.: CB/L, TD-1 B, STD B, R-1 B

Item no.: ASM-580

Dimensions. 220x102x60 cm Gross weight 150 kg



# Bike-Lift®



DARE TO DREAM

## GARDEN 750

MADE IN ITALY



LIFTS



Features a wide tabletop (100 cm) to allow easy maintenance on garden tractors, lawnmowers and vehicles up to 750 kg.

## TECHNICAL DATA

### TECHNICAL SPECIFICATIONS

Vertical scissor system lifting			Tabletop size	215x100 cm
Maximum load capacity	750	kg	Tabletop overall dimensions	220x100 cm
Maximum height	120	cm	Run-up ramp size (two pieces)	84x44,5 cm
Minimum height	19	cm	Overall dimensions	230x100 cm
Safety locking choices	10		Weight	300 kg

### AVAILABLE IN THE FOLLOWING VERSIONS


G-002	EXTERNAL HYDRAULIC AIR PUMP, OPERATED BY A FOOT PEDAL
G-003	BUILT-IN ELECTRO-HYDRAULIC PUMP

### ELECTRO-HYDRAULIC UNIT SPECIFICATIONS

Voltage	230Volt - 50 Hz	Europa
	200Volt - 50/60 Hz	Japan
	110Volt - 60 Hz	USA
Power	1.1 Kw	
Available Switches	Hand Control	Standard
	Foot Control	Upon Request
	Infrared Control	Accessory Item. LC-001

### HYDRO-PNEUMATIC PUMP SPECIFICATIONS

Air pressure	7-10 bar
Air consumption	300 l./min.



### STANDARD EQUIPMENT

2 Run-up ramp – 2 Front safety bar

### ACCESSORIES

Antiskid plate for bikes with centre stand	Item no.: RM, PZA-60/75
Tie downs	Item no.: CB-L, TD-1 B, STD B, R-1 B
Antiskid Plate	Item no.: ASM-580

### STANDARD PACKING

Thick carton box equipped with wood pieces at the bottom

Dimensions. 235x130x30 cm Gross weight 280 kg



# ***Bike-Lift®***



DARE TO DREAM

## **WHEEL CLAMPS**



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)





## WHEEL CLAMPS

MADE IN ITALY



WHEEL CLAMPS



W-36 S



W-38 S



W-32 N



WHEEL CLAMPS	ITEM No.	OPENING RANGE MIN/MAX mm
Automatic	W-36 S	70/205
Automatic	W-38 S	60/170
Pneumatic	W-32 N	55/205

A comprehensive selection of mechanical, pneumatic and automatic wheel clamps designed to meet the requirements of the most demanding technicians. All wheel clamps can be used in combination with our lifts.

## WHEEL CLAMPS

### WHEEL CLAMPS



MADE IN ITALY




W-34



W-40



W-30



WHEEL CLAMPS	ITEM No.	OPENING RANGE MIN/MAX mm
Mechanical	W-34	70/215
Mechanical	W-40	22/225
Mechanical	W-30	70/220

A comprehensive selection of mechanical, pneumatic and automatic wheel clamps designed to meet the requirements of the most demanding technicians. All wheel clamps can be used in combination with our lifts.



# ***Bike-Lift®***



DARE TO DREAM

## **MULTILIFTS**



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)

# ***Bike-Lift®***





## CENTER JACKS


MADE IN ITALY



MULTI LIFTS



MCL-20



MCL-03 A




MCL-30



MCL-IMPORT

100 % Made in Italy



MULTI LIFTS	ITEM No.	DIMENSIONS CM	HEIGHT CM MIN/MAX	CAPACITY KG	KIT ACCESSORIES
Mech. screw threaded	MCL-20	15x40	8/35	400	MCL-03 A
Mech. screw threaded	MCL-IMPORT	15x48	9/35	400	INCLUDED
Mech. screw threaded	MCL-30	25x40	8,5/35	400	
Accessories for MCL-20	MCL-03 A				



## CUSTOM FLOOR LIFT 500

MULTI LIFTS



MADE IN ITALY



**CUSTOM**  
CFL-500



**QUAD**  
CFL-500/Q



MULTI LIFTS	ITEM No.	LIFTING SYSTEM	SAFETY STOPS	HEIGHT CM MIN/MAX	CAPACITY KG
Hydraulic lift for custom bikes	CFL-500	Hydraulic foot pedal	3	8/45	500
Hydraulic lift for custom Quads	CFL-500/Q	Hydraulic foot pedal	3	18/55	500



# ***Bike-Lift®***



DARE TO DREAM

## **OFF ROAD**

[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)

# ***Bike-Lift®***






## OFF-ROAD STANDS

MADE IN ITALY



OFF-ROAD

### KRISS KROSS STAND 130



Height MAX  
36 cm

Height MIN  
26 cm



KKS-130 S

KKS-130



### CROSS STAND 2000



43 cm



CS-2000

OFF-ROAD	ITEM No.	DIMENSIONS CM	HEIGHT CM MIN/MAX	MATERIAL
Centre stand for cross bikes	KKS-130	10x30	29/39	Steel
Centre stand for motard bikes	KKS-130 S	10x30	26/36	Steel
Cross Stand 2000	CS-2000	24x24	43	Aluminium

A comprehensive selection of aluminium and steel stands designed to meet and exceed the expectations of the most demanding off-road enthusiasts.

## ALUMINIUM STANDS

OFF-ROAD

### P-12 STAND P-12



Adjustable in 12 different positions

Height MAX  
from 36 to 45 cm

Height MIN  
from 24 to 33 cm

### P-12 STAND P-12/E



### TRI MOTO STAND TMS

Lateral stand in aluminium for off-road bikes. 3 tapered axle pins accommodate most axle pins (Honda, Yamaha, Suzuki, Kawasaki and KTM)



OFF-ROAD	ITEM No.	HEIGHT MAX/MIN CM	DIMENSIONS CM
P-12 STAND	P-12	24/36 33/45	24x24
P-12 STAND e-version	P-12/E	31,5/40,5	30x16
TRI MOTO STAND	TMS	31,5	27,5


ITALIAN DESIGN MADE IN CHINA



## ALUMINIUM STANDS

OFF-ROAD

### X-STAND SX



### X TOOL TRAY X-TT



43 cm



### PRO PANEL



43 cm

PP



42 cm

PP/E

OFF-ROAD	ITEM No.	HEIGHT MAX/MIN CM	DIMENSIONS CM
X-STAND	SX	43	26x30
X-TOOL TRAY	X-TT	7,5	20x31,5
PRO PANEL	PP	43	24x24
PRO PANEL e-version	PP/E	42	24x24

ITALIAN DESIGN MADE IN CHINA

# Bike-Lift®



DARE TO DREAM

## HANDY LIFT STAND

OFF-ROAD




MADE IN ITALY



Height MAX  
89 cm

Height MIN  
39 cm

HXL-160



Hydraulic lift with foot pedal to raise off-road bikes



## MX STAND 2008

OFF-ROAD



MX-2008



Semi-automatic off-road stand. Simply push or ride the bike onto the lowered lift. As the front tire touches the front plate, the lift goes into action rising to the bottom of the motorcycle frame. Step on the foot pedal and your bike will rise effortlessly into a secure position. Getting your bike down is just as effortless and simple. Just kick the release with the heel of your boot and roll the bike off the lift. Weighing only 12kg, this stand is lightweight, portable and stable in the pits. Each lift comes with a locking pin and is lockable in the up and down position for ease of transport and safety. Front and rear tires, and suspension can be serviced while on the lift. The framework is made of high-strength, powder-coated steel.





# ***Bike-Lift®***




DARE TO DREAM

## **REPAIR-SHOP EQUIPMENT**



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)





## ENGINE STANDS

MADE IN ITALY



REPAIR-SHOP EQUIPMENT



Adapters for scooters' engines



ES-06/AS



ES-06: Universal stand conceived for servicing motorcycles and maxi-scooters (with the addition of the adapters ES-06/AS and ES-06/DUC). Complete 360° rotation. Universal fixing plate for motorcycle engines. Features a special tray for waste oil recovery and wheels with brake.

## REPAIR-SHOP EQUIPMENT

REPAIR-SHOP EQUIPMENT



MADE IN ITALY

### SH.A.DIS. Shock Absorber Disassembler SA-07



#### STANDARD ADAPTERS

Ø 45 mm  
Ø 47 mm  
Ø 50 mm  
Ø 53 mm  
Ø 56 mm  
Ø 59 mm  
Ø 62 mm  
Ø 66 mm  
Ø 68 mm  
Ø 71 mm  
Ø 75 mm  
Ø 77 mm  
Ø 80 mm  
Ø 83 mm  
Ø 87 mm

### ENGINE STAND ES-01



SA-07: universal shock absorbers and forks disassembler.

ES-01: universal stand conceived for servicing all motorcycle engine. Ensure the complete 360° rotation of the engine and its stopping at the most convenient working position.



# ***Bike-Lift®***



DARE TO DREAM

## **TYRES & WHEELS**

***RESET***



**09**

***Weight (gr)***


# ***Bike-Lift®***

***www.ppblift.com***

***Made in Italy***

***WWW.BIKELIFT.NET***

# Bike-Lift®





## TYRE CHANGERS

### TYRES & WHEELS



TCC-523



Pedals



Bead breakers



Plastic demount-head



Steel demount-head



TYRE CHANGERS	ITEM No.	DIMENSIONS CM	WEIGHT KG	VOLT
Semi-automatic with swing-arm column	TCC-523/230	100x100x170h.	220	240
Semi-automatic with swing-arm column	TCC-523/380	100x100x170h.	220	400

Bike-Lift offers a wide range of tire changers, specifically conceived for motorcycles, scooters and quads. All moving parts which somehow touch the rim are supplied with special rubber protections in order to prevent any possible damages.

## TYRE CHANGERS


TYRES & WHEELS



MADE IN ITALY




TCG-523



TCF-523

Pivoting rim clamps



Plastic demount-head



TYRE CHANGERS	ITEM No.	DIMENSIONS CM	WEIGHT KG	VOLT
Semi-automatic with floating arm	TCG-523/230	100x100x180h.	220	240
Semi-automatic with floating arm	TCG-523/380	100x100x180h.	220	400
Automatic with tilting column	TCF-523/230	100x160x170h.	220	240
Automatic with tilting column	TCF-523/380	100x160x170h.	220	400



## MANUAL TIRE BEAD BRAKER

MADE IN ITALY



TYRES & WHEELS



TBB-17/21



KA-7022



KA-7023



TYRE CHANGER	ITEM No.	DIMENSIONS CM	WEIGHT KG
Manual tire bead breaker	TBB-17/21	31x79	12
Demount Bar	KA-7022		
Rim protection	KA-7023		



## WHEEL BALANCERS


TYRES & WHEELS



MADE IN ITALY



B-35



B-35/E



WHEEL BALANCER	ITEM No.	DIMENSIONS CM	WEIGHT KG	VOLT
Static wheel balancer	B-35	48x28x50h.	8	
Electronic wheel balancer	B-35/E	47x36x52h.	12	230
Kit of adapters for single-arm wheels	B-A01			
Adapter for BMW wheels	B-A02			
Kit of adapters for maxi-scooters wheels	B-A03			
Kit of adapters for Piaggio X9	B-A04			
Kit of adapters for BMW 06/07	B-A05			

Made in Italy



B-A01



B-A02



B-A05



B-A03



B-A04





## ELECTRONIC WHEEL BALANCER 723

MADE IN ITALY



TYRES & WHEELS



BM-723



BM-M



WHEEL BALANCER	ITEM No.	DIMENSIONS CM	WEIGHT KG	VOLT
Electronic wheel balancer	BM-723	110x100x115h.	90	230
Kit of adapters for single-arm wheels	BM-M			





# ***Bike-Lift®***



DARE TO DREAM

## **PADDOCK STANDS**



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)





## ERGAL STANDS

MADE IN ITALY



PADDOCK STANDS

RS-17/E



FS-10/E



SAC-10



SAF-10/E




PADDOCK STANDS	ITEM No.	ADDITIONAL INFORMATIONS
Aluminium universal front stand	FS-10/E	In extra light and resistant aluminium. Weight: 2kg
Aluminium universal rear stand	RS-17/E	In extra light and resistant aluminium. Weight: 2kg
Adapters for under fork use	SAC-10	Fits all bikes with openings under the forks
Forked V type adapters	SAF-10/E	In aluminium

## REAR STAND 17


PADDOCK STANDS



MADE IN ITALY




SBG-10



SAF-10



RS-17



NA-M10

NA-M6

NA-M8



PADDOCK STANDS	ITEM No.	ADDITIONAL INFORMATIONS
Universal rear stand	RS-17	Available colours: Red/Blue/Grey/Black/Green
Rubber adapters	SBG-10	
Forked V type adapters	SAF-10	Equipped with special rubber protections
Aluminium bobbins M6	NA-M6	For Yamaha, Aprilia e Triumph
Aluminium bobbins M8	NA-M8	For Suzuki, Honda e Ducati
Aluminium bobbins M10	NA-M10	For Kawasaki



## FRONT STAND 10

MADE IN ITALY



PADDOCK STANDS



FS-10



SAC-10



SAR-10



PADDOCK STANDS	ITEM No.	ADDITIONAL INFORMATION
Universal front stand	FS-10	Available colours: Red/Blue/Grey/Black/Green
Adapters for under fork use	SAC-10	Fits all bikes with openings under the forks
Adapters for special off-line forks.	SAC-10/Y	Fits Yamaha and Kawasaki with off-line forks
Pivoting roller adapters	SAR-10	Universal adapters. Especially recommended for BMW.



## FRONT HEADSTOCK STAND

Paddock Stands



MADE IN ITALY



Paddock Stands	Item No.	Additional Informations
Standard front headstock 6 pins	FS-11	Six interchangeable pins ø: 13 15 17 18 20 27 mm Available colours: Red/Blue/Grey/Black/Green



# Bike-Lift®



## FRONT HEADSTOCK STAND NEW

MADE IN ITALY



PADDOCK STANDS



FS-11/NEW



Universal pin



Plate for Ducati and MV Agusta



### PADDOCK STANDS

Universal front headstock

### ITEM No.

FS-11/NEW

### ADDITIONAL INFORMATION

Supplied with a conical adapter and a plate for MV Agusta and Ducati. Available in red colour only.





2008 News  
New Pin for Honda CB1000R

PMH-CB08



RS-16

PADDOCK STANDS	ITEM No.	ADDITIONAL INFORMATIONS
Single arm stand. Left side	RS-16	Fits all bikes with single sided swing arm. Available colours: Red/Grey/Black
Ducati pin	PMD-01	Fits all Ducati models (except 1098).
Honda CB1000R pin	PMH-CB08	Fits Honda CB1000R
Triumph pin	PMT-01	Fits Speed Triple, Sprint st, 955 Daytona
Honda pin	PMH-01	Fits VFR
MV- Ducati 1098 ø 42 mm pin	PMM-01	Fits MV and Ducati 1098 ø 42 mm
Ducati 1098 ø 40 mm pin	PMD-98/40	Fits Ducati 1098 ø 40 mm
BMW pin	PMB-1200 K	Fits K 1200 S, R, GT and HP2



PMH-01



PMT-01




PMD-01

PMM-01



PMB-1200K



PMD-98/40





# Bike-Lift®



## REAR STAND 16/R

MADE IN ITALY



PADDOCK STANDS



RS-16/R



PMD-01/R

PMB-1200



PMB-650

PMB-1200 K



PADDOCK STANDS	ITEM No.	ADDITIONAL INFORMATIONS
Single arm stand. Right side	RS-16/R	Available colours: Red/Grey
Ducati pin	PMD-01/R	Allows easy sprocket disassembly
BMW F650 CS pin	PMB-650	Usable on F 650 CS only
BMW R1200 GS pin	PMB-1200	Fits R1200 GS, R1200 RT
BMW pin	PMB-1200 K	Fits K 1200 S, R, GT




## CENTER STAND 24



CS-24


PADDOCK STANDS	ITEM No.	ADDITIONAL INFORMATIONS
Centre Stand. Locks onto swinging arm pivot.	CS-24	Available in red colour only.
Shaft Ø 10	CS-10	For centre stand CS-24
Shaft Ø 12	CS-12	For centre stand CS-24
Shaft Ø 15	CS-15	For centre stand CS-24
Shaft Ø 15/8	CS-15/8	For centre stand CS-24



CS-10



CS-12



CS-15



CS-15-8



## FRONT STANDS

MADE IN ITALY



Paddock Stands



FS-9



FS-10/H

Special for bikes with radial brakes.



Paddock Stands	Item No.	Additional Informations
Universal front fixed stand.	FS-9	Available colours: Red/Blue/Grey/Black/Green
Front stand for bikes with radial-mount brake calipers. High version.	FS-10/H	Recommended for MV Agusta and bikes with radial .brakes. Available in red colour only.



## SPECIAL REAR STANDS

### Paddock Stands



MADE IN ITALY

#### RS-17/L

Special for Suzuki 2006/2007



#### RS-17/TB

Special for Triumph Bonneville



#### RS-17/D

Special for Ducati 749/999 2004/2005

### Paddock Stands

Low rear stand with SAF-10

### ITEM No.

RS-17/L

### ADDITIONAL INFORMATION

Recommended for Suzuki 2006/2007 with low swing arm pivot. Available only in red colour.

Bonneville rear stand

RS-17/TB

Special version Triumph Bonneville. Available colours: Red/Blue/Silver

Ducati rear stand

RS-17/D

Usable on Ducati 749/999 2004/05 only. Available in red colour.




# ***Bike-Lift®***



DARE TO DREAM

## **GARAGE & TRAILERS**

# ***e-Lift***



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)





# Bike-Lift®



DARE TO DREAM

## WHEEL PARKING 400

MADE IN ITALY



GARAGE & TRAILERS

SE-400



WP-400



GARAGE & TRAILERS	ITEM No.	CAPACITY KG	DIMENSIONS CM
Wheel Parking 400	WP-400	400	46x51
Side Extension	SE-400	400	13x86

Ideal for manoeuvring motorcycles in tight spaces. Perfect for use in home garages or dealer show-rooms. Usable on all bikes with centre stand. Combined with the side extension SE-400, fits all bikes with side stand



## WHEEL CLAMPS

GARAGE & TRAILERS



MADE IN ITALY



W-36 F



W-38 C



GARAGE & TRAILERS	ITEM No.	OPENING RANGE MIN/MAX mm
Automatic wheel clamp for vans	W-36 F	70/205
Automatic wheel clamp for trailers	W-38 C	95/150

The model W-36 F allows one single person to load the bike on the van and fix it firmly. Just two straps on the rear hold the bike securely. The model W-38 C is conceived for use on trailers only.




# ***Bike-Lift®***



DARE TO DREAM

## **RAMPS & TIE-DOWNS**



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)

# ***Bike-Lift®***





## RAMPS

### RAMPS & TIE-DOWNS

MOTO RAMP  
MR-180  
MR-240




U-RAMP  
UR



Three models (MR-180, MR-24 and U-Ramp) are totally dedicated to the off-road world.

The folding model (Ramp-4000) is conceived for all bikes up to 400 kg.

SPORT RAMP  
RAMP-4000



ALUMINIUM RAMPS	ITEM No.	CAPACITY KG	LENGTH CM	WIDTH CM
One-piece ramp for off-road bikes	MR-180	160	180	13,7
One-piece ramp for off-road bikes	MR-240	160	240	13,7
Folding ramp for off-road bikes	UR	160	240	13,7
Folding ramp for sport bikes	RAMP-4000	400	240	28

## TIE-DOWN STRAPS

RAMPS & TIE-DOWNS



STD B



TD-1B



R-1 B



TIE-DOWN STRAPS	ITEM No.	PIECES	LENGTH CM	WIDTH CM
Two S-style hooks	TD-1B	2	164	2,5
Two S-style hooks hand loop for pulling tight	STD B	2	172	2,5
Two S-style hooks with adjustable ratchet	R-1 B	2	178	2,5



# ***Bike-Lift®***



DARE TO DREAM

## **RACING**

[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)



**HONDA GRESINI RACING TEAM**



**TROFEO SUPER DUKE KTM**



**STOP AND GO RACING TEAM**



# Bike-Lift®



## ALUMINUM BENCH

MADE IN ITALY



RACING




RACING	ITEM No.	CAPACITY KG	DIMENSIONS CM
Aluminium Bench	AL-BN	400	200x60x55h.
Run-up ramp			200x23

## RACING STANDS

RACING



MADE IN ITALY



RS-100: Aluminium racing rear stand with painted steel tubes. Dismountable in three parts. Supplied with forked V type adapters.

FS-100: Aluminium racing front stand for under radial brakes use with painted steel tubes. Dismountable in three parts. Supplied with rubber adapters.




# ***Bike-Lift®***



DARE TO DREAM

## **GAS EXTRACTION**



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)





## SPRING RECOIL EXHAUST

GAS EXTRACTION



AR-75/5D  
AR-75/7.5D  
ARC-100/5D  
ARC-100/7.5D



ARA-75/7PB-SB  
ARCA-100/7PB-SB

To complete these systems, add one of the nozzles listed in the catalogue.



ITEM No.	HOSE	HOSE CLAMP COVER	HOSE CLAMP	ELECT. EXTRACTION FAN	POWER
AR-75/5D	1 L=5m Ø75 mm	1 COPRI-FSC 75	AFT 75	NON INCLUSO	-
AR-75/7.5D	1 L=7,5m Ø75 mm	1 COPRI-FSC 75	AFT 75	NON INCLUSO	-
ARC-100/5D	1 L=5m Ø100 mm	2 COPRI-FSC 100	AFT 100	NON INCLUSO	-
ARC-100/7.5D	1 L=7,5m Ø100 mm	2 COPRI-FSC 100	AFT 100	NON INCLUSO	-
ARA-75/7PB-SB	1 L=7m Ø75 mm	2 COPRI-FSC 75	AFT 75	INCLUSO	230/400V -3PH 50 HZ KW0.37/HP0.5 out ø150mm
ARCA-100/7PB-SB	1 L=7m Ø100 mm	2 COPRI-FSC 100	AFT 100	INCLUSO	230/400V -3PH 50 HZ KW0.37/HP0.5 out ø150mm

Supplied with EUROGAS hose, heat-resistant up to temperatures of 200°C.



## MOTOR DRIVEN EXHAUST

GAS EXTRACTION



AMTA-75/7.5SB



AMT-75/7.5D

To complete these systems, add of one of the nozzles listed in the catalogue.




**AMT-75/7.5D:** Reel complete with EUROGAS crushproof flexible hose, AFT 75 hose stop, 2 hose clamps and COPRI-FSC-75 hose clamp covers. With 7.5 metre length of 75 mm Ø hose. Automatic adjustable travel stop and provision for automatic extraction fan startup.

**AMTA-75/7.5 SB:** Reel complete with EUROGAS crushproof flexible hose, AFT 75 hose stop, 2 hose clamps and COPRI-FSC-75 hose clamp covers. With 7.5 metre length of 75 mm Ø hose. Automatic adjustable travel stop and provision for automatic extraction fan startup. Combined with extraction fan, 230/400v ~3PH 50 HZ 0.37kW/0.5 HP- 150mm Ø outlet



## ELECTRICAL EXTRACTION FAN

GAS EXTRACTION



Electrical extraction fan in sheet steel housing, complete with inlet and outlet hose connections.

AL-50/C  
AL-100/C  
AL-150/C  
AL-200/C



**AL-50/C:** Extraction fan with airflow 300-900 m<sup>3</sup>/h (Max. press. 105 mm H<sub>2</sub>O) – 0.37kW / 0.5 HP - 230/400 V - 50 Hz. 150 mm ø inlet and outlet (R)

**AL-100/C:** Extraction fan with airflow 300-900 m<sup>3</sup>/ 700-1.700 m<sup>3</sup>/h (Max. press. 95 mm H<sub>2</sub>O) – 0.75 kW / 1 HP - 230/400 V - 50 Hz. 180 mm ø inlet and outlet (R)

**AL-150/C:** Extraction fan with airflow 300-900 m<sup>3</sup>/ 1.000-2.100 m<sup>3</sup>/h (Max. press. 145 mm H<sub>2</sub>O) – 1.1 kW / 1.5 HP - 230/400 V - 50 Hz. 180 mm ø inlet and outlet mm (R)

**AL-200/C:** Extraction fan with airflow 300-900 m<sup>3</sup>/ 1.700-3.000 m<sup>3</sup>/h (Max. press. 165 mm H<sub>2</sub>O) – 1.5 kW / 2 HP - 230/400 V - 50 Hz. 200 mm ø inlet and outlet (R).



## ACCESSORIES FOR EXHAUST HOSE REELS

GAS EXTRACTION


BG-75/140  
BG-75/200



Y75-BGT-75/140  
Y100-BGT-75/140  
Y100-BGT-75/200



BRM-75/140  
BRM-75/200  
BRM-100/140



BRMS-75  
BRMS-100



BCA-250



**BG:** Oval nozzle in non-scratch rubber for 75mm Ø hose, 32mm Ø inlet for CO tester.

**BG-75/140:** Ø140mm **BG-75/200:** Ø200mm

**Y-BGT:** Y-shaped double nozzle adaptor complete with Eurogas flexible hose. **Y75-BGT-75/140:** Ø75L nozzles BGT-75/140. **Y100-BGT-75/140:** Ø100L nozzles BGT-75/140. **Y100-BGT-75/200:** Ø100L nozzles BGT-75/200.

**BRM:** Conical nozzle in non-scratch rubber mounted on stand with height and tilt adjustment.

**BRM-75/140:** attacco Ø75mm con BGT-75/140. **BRM-75/200:** attacco Ø75mm con BGT-75/200

**BRM-100/140:** for 100 mm Ø hose with BGT-75/140

**BRMS:** Conical nozzles in non-scratch rubber with double height and tilt adjustable stand, trolley-mounted base.


**BRMS-75:** attacco Ø75mm. **BRMS-100:** attacco Ø100mm.

**BCA-250:** Oval nozzle mounted on stand with height and tilt adjustment. For 100mm Ø hose.



## ACCESSORIES FOR EXHAUST HOSE REELS

### GAS EXTRACTION



### MICRO-START

For use with all spring recoil hose reels without extraction fans.



### MICRO-CTRL

For use with all spring recoil hose reels with combined extraction fans.

ALLUFLEX-120  
ALLUFLEX-150



ATR/75  
ATR/100



EUROGAS-75/7.5  
EUROGAS-100/7.5



ATR/B-75  
ATR/B-100



SM-20

**MICRO-START:** Microswitch for spring recoil hose reels. Essential for automatic startup/stop of a centralised extraction fan. Requires one MICRO-START for each hose reel and one QE-AC for the extraction fan.

**MICRO-CTRL:** Control system for ACA-ARA with 400v 50/60Hz extraction fan – Max. power 1.5 Hp. Movement control/automatic stop by extending/pulling on flexible hose. For ARA-75/7PB-SB and ARCA-100/7PB-SB.

**ALLUFLEX:** Non-welded flexible aluminium hose, extends to 3 metres. max. operating temperature: 300°C.  
**ALLUFLEX-120:** Ø120mm. **ALLUFLEX-150:** Ø150mm.

**EUROGAS:** Crushproof steel reinforced hose, Top series, 7.5 metre length. **EUROGAS-75:** Ø75mm. **EUROGAS-100:** Ø100mm.

**ATR:** PVC pressure joint for EUROGAS hoses. **ATR/75:** Ø75mm. **ATR/100:** Ø100mm.

**ATR/B:** Connection joint for nozzles and EUROGAS hoses. **ATR/B-75:** Ø75mm. **ATR/B-100:** Ø100mm

**SM-20:** Wall-mounted hose support.




### GAS EXTRACTION

ECOSYS-A-../2



ECOSYS-A-../1



ITEM No.	HOSE	TRACK	SLIDING TROLLEY	ELECTRICAL EXTRACTION FAN	OUT
ECOSYS-A-06/1	Ø75mm L= 7,5m	6m	1	1HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-06/2	Ø75mm L= 7,5m	6m	2	1,5HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-09/1	Ø75mm L= 7,5m	9m	1	1HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-09/2	Ø75mm L= 7,5m	9m	2	1,5HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-12/1	Ø75mm L= 7,5m	12m	1	1HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-12/2	Ø75mm L= 7,5m	12m	2	1,5HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-15/1	Ø75mm L= 7,5m	15m	1	1HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-15/2	Ø75mm L= 7,5m	15m	2	1,5HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-18/1	Ø75mm L= 7,5m	18m	1	1HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-18/2	Ø75mm L= 7,5m	18m	2	1,5HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-21/1	Ø75mm L= 7,5m	21m	1	1HP-0,75kW - 230/400v - 50 HZ	180-R
ECOSYS-A-21/2	Ø75mm L= 7,5m	21m	2	1,5HP-0,75kW - 230/400v - 50 HZ	180-R

Complete exhaust gas extraction system comprised of:

Extruded aluminium track, model ETK1 (equiv. Ø 151mm) in various lengths

Universal sliding trolleys (1 or 2)

2 closed flanges

Upper outlet flange connected to the extraction fan via ALLUFLEX-180 hose

1 set of accessories for installation of the extraction fan directly on the track

Electrical extraction fan in sheet steel housing (specifications vary)

Sliding trolleys for Ø75mm hose (1 or 2) complete with reinforced crushproof EUROGAS Ø75mm hose, heat-resistant up to temperatures of 200°C

Rubber nozzle with cap BGT-75/140

Hose supports with rubber sleeve with spring clip



## ECOSYSTEM

### GAS EXTRACTION



**CSETK-75/7-COMP:** Trolley with EUROGAS75/7.5m hose; CSZR-CAR, BGT-75/140 nozzle.

**BL-A:** Universal balance block with nautical cord for suspended flexible hose.

**BLS-EKT-SUP:** Support for BL-A universal balance block for CSETK series trolleys



**QE-AC1T/1.5HP:** electrical control panel centralised 400v 1.5HP 1.1kW extraction fan, complete with 2-channel receiver and remote control.

**ALLUFLEX:** 1 metre length of 180mm Ø flexible seamed aluminium hose, fireproof and extendible to 3metres. Max. operating temperature: 300°C



## COMPLETE WALL-MOUNTED EXTRACTION KIT

### GAS EXTRACTION

Complete exhaust gas extraction system comprising: extraction fan, hose/s (1 or 2), rubber nozzle/s (1 or 2) and wall-mounted support/s (1 or 2).



ARGON-1-75-5  
ARGON-1-75-7

ECOARG-1-75/5  
ECOARG-1-75/7,5



ARGON-2-75-5  
ARGON-2-75-7

ECOARG-2-75/5  
ECOARG-2-75/7,5



ITEM No.	EUROGAS-75	BGT-75 /140	ECOARGON/SM	EXTRACTION FAN	OUT
ARGON-1-75-5	1 L=5m	1	1	0.5HP - 230/400v - tri-phase	150-R
ARGON-2-75-5	2 L=5m	2	2	0.5HP - 230/400v - tri-phase	150-R
ARGON-1-75-7	1 L=7,5m	1	1	0.5HP - 230/400v - tri-phase	150-R
ARGON-2-75-7	2 L=7,5m	2	2	0.5HP - 230/400v - tri-phase	150-R
ECOARG-1-75/5	1 L=5m	1	1	0.5HP - 230/400v - tri-phase	75-L
ECOARG-2-75/5	2 L=5m	2	2	0.5HP - 230/400v - tri-phase	75-L
ECOARG-1-75/7,5	1 L=7,5m	1	1	0.5HP - 230/400v - tri-phase	75-L
ECOARG-2-75/7,5	2 L=7,5m	2	2	0.5HP - 230/400v - tri-phase	75-L



## MOBILE EXTRACTION FAN

GAS EXTRACTION



TROTTER-100/S



TROTTER-50

To complete these systems, add of one TROTT.100-TUBO



ECOBP-6000GAS

**ECOBP-6000GAS:** tilting arm ARTIC L=6000 mm+AJ-75 + TUBOFLEX 75/5+BGT 75+ASZ755

**TROTTER-50:** Mobile fan for the exhaust gas extraction from the working area.

Airflow higher than 1000 m<sup>3</sup>/h. Max. pressure 105mm H<sub>2</sub>O - 400V - 3PH 50Hz KW0.37/HP0.5 - out ø 100-L

**TROTTER-100/S:** Mobile extraction fan adjustable in height and inclination. Ideal for power tests. Max. airflow 1900 m<sup>3</sup>/h, max. pressure 95mm H<sub>2</sub>O - 400V - 3PH 50Hz KW0.75/HP1 - out ø 150-L





# ***Bike-Lift®***



DARE TO DREAM

## **ACCESSORIES**

***Bike-Lift***

[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)

# Bike-Lift®



DARE TO DREAM






## ACCESSORIES


### CARGOBUCKLE® CB/L



### INFRARED CONTROL LC-001



RA-20



RA-40



RA-60

ACCESSORIES		ITEM No.	PIECES N°	WIDTH CM	LENGTH CM
Vulcanized rubber adapter.	H. 20	RA-20	1	11	14
Vulcanized rubber adapter.	H. 40	RA-40	1	12	16
Vulcanized rubber adapter.	H. 60	RA-60	1	11,5	16
CARGOBUCKLE®		CB/L	1	5	134
Retractable tie-down system with built-in ratchet					



## ACCESSORIES


### ACCESSORIES

#### ANTISKID PLATFORM


RM-60




PZA-60



#### ANTI-FATIGUE MAT




AFM-15



Nitricell® sponge base



AFM-25



Nitricell® sponge base







## ACCESSORI

## ACCESSORIES


### SIDE EXTENSION WINGS



### ANTISKID MAT FOR RUN-UP RAMPS



### SW-500 (MAX 500 - MAX 500 GATE)



### SW-750 (CRUISER 750 GATE)



ACCESSORIES	ITEM No.	DIMENSIONS CM
Set of side extension wings for Max 500 and Max 500 Gate	SW-500	28x210
Set of side extension wings for Cruiser 750 Gate	SW-750	28x220
Antiskid mat for Run-up Ramps	ASM-580	30x58






# ***Bike-Lift®***



DARE TO DREAM

## **PROFI PRODUCTS**





[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)

## PROFI PRODUCTS

### PROFI B A T LASER BIKE ALIGNMENT TOOL



PROFI BAT



### PROFI S-BAT LASER SPORTBIKE ALIGNMENT TOOL



PROFI S-BAT



### PROFI Q A T LASER QUAD ALIGNMENT TOOL




PROFI QAT



### PROFI C A T LASER CHAIN ALIGNMENT TOOL

PROFI CAT





# ***Bike-Lift®***



DARE TO DREAM

## **WORKSHOP FURNITURE**

[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)

# ***Bike-Lift®***





# Bike-Lift®




DARE TO DREAM

## 7-DRAWER ROLL CAB

WORKSHOP FURNITURE




T-7C




Overall dimensions: 75x45x100 cm.



Dimensions No. 5 drawers:



Dimensions No. 2 drawers:






# Bike-Lift®



## WORK BENCH WOODEN TABLETOP WORKSHOP FURNITURE




T-13C


Overall dimensions: 120x47x100 cm.




Dimensions No. 1 drawe:



Dimensions No. 5 drawers::



Dimensions No. 1 drawer:





## MODULAR CHEST OF DRAWERS

WORKSHOP FURNITURE




SET OF DRAWERS


RC-155



ROLL CAB



Overall dimensions 120x44,5x55 cm



Overall dimensions 120x46x100 cm

Chest of drawers composed of:

No. 1 drawer	102x43x7 cm
No. 3 drawers	57x40x5 cm
No. 1 drawer	57x40x13 cm
No. 3 drawers	30x40x5 cm
No. 1 drawer	30x40x13 cm

Work bench composed of:

No. 1 drawer	93,5x40x10 cm
No. 5 drawers	56,5x40x5,5 cm
No. 1 drawer	56,5x40x13,5 cm
No. 1 door	43,5x41,5x56 cm



## WORK BENCHES

WORKSHOP FURNITURE

WS-1500



WS-2000



ITEM No.	LENGTH CM	WIDTH CM	HEIGHT CM	DRAWERS	DRAWERS DIMENSIONS	SHELF DIMENSIONS
WS-1500	150	64	87	2	35x42x11,5 cm	120x50 cm
WS-2000	200	64	87	3	35x42x11,5 cm	170x50 cm



## WORK BENCHES

### WORKSHOP FURNITURE



GR08



GR07



GR10  
GR11  
GR12



ITEM No.	LENGTH CM	WIDTH CM	HEIGHT CM	THICKNESS MM	KG
GR07	100	65	88	3	33
GR08	150	65	88	3	58
GR09	200	65	88	3	74
GR10 wooden tabletop	100	65	88	3	39
GR11 wooden tabletop	150	65	88	3	68
GR12 wooden tabletop	200	65	88	3	87

Modular workbenches, as illustrated in the enclosed drawings.


GR13



GR13-G



GRCB





## EXAMPLES

### WORKSHOP FURNITURE

GR07+GR13



GR07+GR13-G




GR08+GR13




GR08+GR13-G



GR09+GR13+GRCB



GR09+GR13-G+GRCB



GR09+GR13+GR13



GR09+GR13-G+GR13-G



### WORKSHOP FURNITURE

#### TOOLHOLDER PANELS GR15 GR16 GR17



#### TOOLS TROLLEY



GR04 (2 shelves)  
GR05 (3 shelves)


#### HOOKS GR19-A



GR18 70mm



GR19 100mm



ITEM No.	LENGTH CM	WIDTH CM	HEIGHT CM	THICKNESS MM	Ø WHEELS CM	KG
GR04	82	42,5	78	1,5	10 with brake	16
GR05	82	42,5	78	1,5	10 with brake	22
GR15	100	-	83	-	-	6
GR16	150	-	83	-	-	9
GR17	200	-	83	-	-	12



## HYDRAULIC BEARING PRESS

WORKSHOP FURNITURE

HG-20




Height  
180 cm

Height  
106 cm

HG-10




Hydraulic bench press 10 TON



PRESS	ITEM No.	DIMENSIONS CM	HEIGHT CM	CAPACITY
Bearing press 20 TON	HG-20	74x70	180	20 TON
Bearing press 10 TON	HG-10	59x45	106	10 TON

## ENGINE CRANE

WORKSHOP FURNITURE



Engine crane with hydraulic pump for maximum safety whilst lifting heavy loads during normal maintenance on vehicles.




# ***Bike-Lift®***



DARE TO DREAM

## **PROFESSIONAL TOOLS**



[WWW.BIKELIFT.NET](http://WWW.BIKELIFT.NET)



# Bike-Lift®





## SPANNERS & WRENCHES

### PROFESSIONAL TOOLS

71592



2 piece metric combination spanner set. Forged from chrome vanadium steel, hardened, tempered, chrome plated and fully polished throughout. Contents: 8 - 9 - 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 and 19mm.

71593



5 pc reversible gearwrench set. Expert Quality, open end set at 15° and Draper Expert HI-TORQ ratchet ring end offset at 15°. Contents: 10, 12, 13, 17 and 19mm

71595



5 pc flexible gear wrench set. The Draper Expert HI-TORQ flexible head allows movement through 180°. Contents: 10, 12, 13, 17 and 19mm

68068



12 pc reversible gearwrench forged from chrome vanadium steel, in blister. Contents: 8 - 9 - 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 and 19mm.

68234



11 pc comb. spanner set forged in chrome vanadium steel, in blister. Contents: 7 - 8 - 10 - 11 - 12 - 13 - 14 - 15 - 17 - 18 and 19mm.

71247



7 pc flexible head gearwrench forged from chrome vanadium steel, in blister. Contents: 10 - 12 - 13 - 14 - 15 - 17 and 19mm.

64607



8 pc metric spanner set forged in chrome vanadium steel, in blister. Contents: 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19 and 20x22mm.





## SPANNERS AND WRENCHES

### PROFESSIONAL TOOLS

69913



35pc set packed in blow mould tray, ideal for toolbox drawer storage.  
 11 Draper Expert HI-TORQ: 4,0; 5,0; 5,5; 6,0; 7,0; 8,0; 9,0; 10,0; 11,0; 12,0 and 13,0mm  
 6 Draper Expert HI-TORQ: 6,0; 7,0; 8,0; 10, 12 and 13mm  
 1 reversible ratchet with quick release button  
 2 extension bars size: 50 and 100mm  
 1 tee bar head/ 3/8" (F) x 1/4" (M) converter  
 1 universal joint  
 1 spinner handle  
 1 bit holder 1/4" sq. drive x 1/4" hexagon  
 2 plain slot insert bits size: 4.0 and 5.5mm  
 2 cross slot insert bits: No.1 and 2  
 2 PZ TYPE insert bits: No.1 and 2  
 2 hexagon insert bits: 5.0 and 6.0mm  
 3 Draper TX-STAR insert bits: T10, T15 and T20  
 1 Tee bar head/converter when used with extension bar forms a sliding tee bar

69914



Expert Quality, manufactured from chrome vanadium steel, hardened, tempered, chrome plated and polished for corrosion protection. Packed in blow mould tray, ideal for tool cabinet arrangements or tool box storage.  
 13 Draper Expert HI-TORQ 12 point sockets size: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 and 22mm  
 1 reversible ratchet with "quick release" button  
 1 extension bar size: 75mm  
 1 sliding tee bar  
 1 universal joint  
 1 3/8"(F) x 1/4"(M) converter

69915



5 pc. 1/2" sq. drive socket accessories set  
 Expert Quality, manufactured from chrome vanadium steel, hardened, tempered, chrome plated and polished for corrosion protection. Packed in blow mould tray, ideal for tool cabinet arrangements or tool box storage.

Contents:  
 1 reversible ratchet with "quick release" button  
 2 extension bars: 125 and 250mm  
 1 tee bar head /1/2"(M) x 3/8"(F) converter  
 1 universal joint  
 1 Tee bar head/converter when used with extension bar forms a sliding tee bar

69916



17 pc 1/2" metric socket set.  
 Expert Quality, manufactured from chrome vanadium steel, hardened, tempered, chrome plated and polished for corrosion protection. Packed in blow mould tray, ideal for tool cabinet arrangements or tool box storage.

Sockets size: 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30 e 32mm





## SPANNERS & WRENCHES

### PROFESSIONAL TOOLS

12447



1/4" square drive sliding tee bar.

57074



4 pc 1/4" square drive wobble extension bar set  
Contents: 50, 100, 150 and 250mm.

13035



8 pc 1/4" square drive HI-TORQ hexagon socket set on socket rail.  
Contents: 5, 6, 7, 8, 9, 10, 12 and 13mm.

12452



1/4" square drive universal joint

32997



9 pc 1/4" 3/8" & 1/2" square drive wobble extension bar set.  
1/4" square drive: 50, 100 and 250mm long  
3/8" square drive: 45, 75, 150 and 230mm long  
1/2" square drive: 125 and 250mm long

35381




14 pc set TX-STAR sockets on rail  
1/4" sq. drive: E4, E5, E6, E7 and E8  
3/8" sq. drive: E10, E11, E12 and E14  
1/2" sq. drive: E16, E18, E20, E22 and E24

64609



8 pc metric double open ended spanner set.  
Contents: 6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19 and 20 x 22mm



## SPANNERS & WRENCHES

### PROFESSIONAL TOOLS

19070



10 pc 3/8" square drive HI-TORQ bi-hexagon sockets on rail.  
Contents: 8, 9, 10, 11, 12, 13, 14, 15, 17 and 19mm.

19798



5 pc 3/8" square drive wobble extension bar set  
Contents: 45, 75, 150, 250 and 450mm long.

13199



3/8" square drive sliding tee bar.

13207



3/8" square drive universal joint

30751



23 pc 1/2" square drive metric HI-TORQ sockets  
Contents: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 30 and 32mm.

19799



4 pc 1/2" square drive wobble extension bar set.  
Contents: 50, 125, 250 and 500mm.

13256



250MM 1/2" square drive sliding tee bar.

13263



1/2" square drive universal joint.



## SPANNERS & WRENCHES

### PROFESSIONAL TOOLS

58130



3/8" square drive precision torque wrench.  
Length: 250 mm. Range 5-22Nm  
Manufactured and calibrated to ISO6789-1992-12-01  
Standard

58138



1/2" square drive precision torque wrench.  
Length: 420mm. Range: 30-100Nm.  
Manufactured and calibrated to ISO6789-1992-12-01  
Standard

58139




1/2" square drive precision torque wrench. Length: 520mm.  
DRIVE PRECISION TORQUE WRENCH. Range: 50 and  
180Nm. Manufactured and calibrated to ISO6789-1992-  
12-01 Standard

59257



8 pc T handled hexagon & ball end hexagon key set.  
Contents: 2 - 2,5 - 3 - 4 - 5 - 6 - 8 and 10mm.

72791-6



8mm T handle socket wrench. Contents: 8 - 10 - 12 - 13 -  
14 and 17mm.

59258



9 pc T HANDLE TX-STAR key set.  
Contents: T10 - T15 - T20 - T25 - T27 - T30 - T40 - T45  
and T50.



29595



10 pc metric ball end hexagon key set  
Contents: 2 - 2,5 - 3 - 4 - 5 - 5,5 - 6 - 7 - 8 and 10mm.

### PROFESSIONAL TOOLS

**38999**



4 pc internal and external circlip plier set.  
180mm straight tip internal circlip pliers  
170mm 90° tip internal circlip pliers  
180mm straight tip external circlip pliers  
170mm 90° tip external external circlip pliers

**88293**



3 pc soft grip self grip pliers set  
Contents:  
•210 and 170mm curved jaw  
165mm long nose

**89901**



250MM heavy duty soft grip waterpump pliers. Seven position adjustment. 'Has 'no-nip' feature which prevents handles locking together when at largest capacity and damaging users' hands. Display packed.

**44152**



4 pc set of heavy duty soft grip pliers in insert tray.  
180mm Combination Pliers  
200mm Long Nose Pliers  
160mm Diagonal Side Cutters  
250mm Waterpump Pliers

**88598**



3 pc soft grip adjustable wrench set. Contents: 150 – 200 and 300mm.

**69287**



2 pc long reach plier set.  
280mm Long Reach Long Nose Pliers  
280mm Bent Nose Long Reach Long Nose Pliers

**38896**



250mm wire twisting pliers.





## SCREWDRIVERS

### PROFESSIONAL TOOLS



**56773**



16 pc screwdriver set with satin chrome plated finish and sand blasted tips. The handle is manufactured from impact-resistant heavy duty 'soft grip' polypropylene with colour coded handles for easy recognition.

**67866**



250mm no 1 PZ TYPE long mechanics screwdriver

**67867**



250mm no 2 PZ TYPE long mechanics screwdriver

**71838**



5 pc engineers/mechanics driver set in insert tray, tempered and satin chrome plated finish with sand blasted tips. The handle is manufactured from impact-resistant heavy duty 'soft grip' polypropylene with colour coded handles for easy recognition.

## GENERAL TOOLS

### PROFESSIONAL TOOLS

39669



Pick-Up Tool

60792



Digital multimeter with light

52305



56cm flexible magnetic pick up tool.  
Chrome plated flexible shaft with plastic handle and removable protective cap over magnet

44945



6 pc soft grip pin punch set.  
Contents: 2x165, 3x175, 4x185, 5x200, 6x200mm and 8x210mm.

44963



200mm soft grip engineers file set.  
Contents: flat, half round and round

44946



6 pc soft grip chisel and punch set.

13039



12 pc cold chisel and punch set.

59985



61 pc socket and screwdriver bit set.



## GENERAL TOOLS

37871



Oil filter wrench

37324



Dead blow hammer, ideal for heavy and effective blows.

72027



Soft faced hammer. The head is supplied complete with 38mm ø faces of soft plastic and nylon. The unbreakable nylon handle has a nonslip PVC grip.  
72028: nylon face (spare part)  
72029: soft plastic face (spare part)

56332



Magnetic parts tray. For storage of nuts, bolts, screws, etc. whilst working, has magnetic base for affixing to metal objects such as vehicle bodywork, tool boxes etc. Ideal for lifts and work benches.

## PROFESSIONAL TOOLS

73996



20 blade metric feeler gauge set. L=100mm.  
Sizes: 0,05 - 1,0mm.

89718



150mm soft jaws for engineers vices.  
Ideal for item 45232

45232



Engineers bench vice. Cast iron body.

40143



Oil & water drain pan.

## GENERAL TOOLS

### PROFESSIONAL TOOLS

**35100**



5 pc scraper and remover set.

**88606**



300mm soft grip hacksaw frame.  
19345: 2 x 300mm hacksaw blades (spare part)

**79366**



21 pc metric tinanium twist drill set.  
Sizes: 1-10mm.

**69292**



150mm mini saw with powder coated frame.  
69305: 10 x junior hacksaw blades (spare part)

**43696**



25 pc metric HSS twist drill set.  
Sizes: 1-13mm.

**47557**



24 led inspection lamp.

